

 **Kawasaki**

**750 MACH IV** MODEL **H2**




# Superperformance.

There is no other 750 as powerful,  
quick or dedicated to performance.




750 MACH IV model H2




Engine kill switch, disc brake lever and reservoir.



Compact tool kit in tail housing.



Rear brake lining wear indicator.



Two colours available: green/lime and brown/gold.



## SPECIFICATIONS

### PERFORMANCE

Maximum horsepower	71 hp/6,800 rpm
Maximum torque	7.9 kg-m/6,500 rpm (57.1 ft-lb/6,500 rpm)
Acceleration	SS 400 m (1/4 mile): 12.0 sec.
Minimum turning radius	2.4 m (94.5 in.)
Fuel consumption	30 km/l @48 kph (85 mile/Imp.gal. @30 mph)
Braking distance	12 m@50 kph (40 ft @31 mph)

### ENGINE

Type	2-stroke, 3-cylinder, piston valve
Displacement	748 cc (45.63 cu.in.)
Bore and stroke	71 x 63 mm (2.795 x 2.48 in.)
Compression ratio	7.0 : 1
Ignition system	Electronic CDI
Starting system	Kick
Lubrication	Injectolube (oil injection)
Engine oil	2-stroke oil

### TRANSMISSION

Type	5-speed, constant mesh, return shift
Shift pattern	N-1-2-3-4-5
Clutch	Wet, multi-disc

### FRAME

Type	Tubular, double cradle
Suspension: Front	Telescopic fork
Rear	Swing arm
Tyre size: Front	3.25 - 19 4PR
Rear	4.00 - 18 4PR

### DIMENSIONS

Length, overall	2,150 mm (84.6 in.)
Width, overall	860 mm (33.9 in.)
Height, overall	1,180 mm (46.5 in.)
Wheelbase	1,435 mm (56.5 in.)
Ground clearance	160 mm (6.3 in.)
Dry weight	205 kg (451 lbs.)
Fuel tank capacity	17 litres (3.7 Imp.gal.)
Oil tank capacity	2 litres (1.8 Imp.qt.)

*Specifications subject to change without notice.*

**KAWASAKI**  
HEAVY INDUSTRIES, LTD.  
MOTORCYCLE DIVISION